

This sleek, economical emergency light offers a contemporary look for lighting and design. Low-maintenance and easy operation makes the DLM an unbeatable model.

- Offers a push-to-test switch, low-voltage disconnect
- Remote capable model available
- E-Z quick connect for fast installation
- UL listed for damp locations

Transfer/Charging Circuitry

Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Warranty

Five year warranty on all electronics and housing. Batteries pro-rated for five years.

Electrical

Dual 120V/277V voltage. Optional multi-tap 208/220/240 voltage available. Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for damp locations (0°C – 50°C).

Housing

Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

Mounting

Surface mount via easy connect back plate, which fits most standard junction boxes and snaps into place making internal electrical connections. Knockout for conduit applications. Suitable for wall or ceiling mount.

Options

SD: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and Life Safety Codes. **HL:** 12-LEDs per head provide increased center-to-center spacing. **SV:** UL Listed for special voltage option.

Battery

3.6V long life, maintenance-free, rechargeable NiCd battery.

Illumination

Long lasting, efficient ultra-bright white LED lamp heads. 1W (8 LEDs x 0.125 watt) per head. High-performance chrome-plated metallized reflector and plastic lens for optimal light distribution. Adjustable LED lamp heads provide optimal center-to-center spacing. High-lumen option available for increased center-to-center spacing.

DLM Series Ordering Information

Series	Housing Color	Options
DLM	W = White B = Black	HL = High Lumen SD = Self Diagnostics SV = 208/220/240 multi-tap voltage in 50/60Hz ¹ RC = Remote Capable

¹Not available with SD units.

Note: Refer to page 24 when ordering RC or SD options for corresponding models.

Dimensions

