



**[ IE28-430AT ]**

**4.0" NPT x (2)3.0" NPT - Angled Recessed Brass FDC w. Double Drop Clappers**



**INFORMATION**

Wilson and Cousins' **IE28-630AT** is a recessed style angled (90-Degree) siamese connection with a 500 GPM inlet capacity, and features a single 4.0" (DN100) NPT outlet and two 3.0" (DN80) NPT inlets . The cast brass body can be used as an auxiliary connection to supplement fire protection water supply systems. and is rated for working pressures up to 250 psi. This connection, with dual independent self-closing clapper valves, can be concealed inside of a building wall during construction. UL/ULC Approved.


**FINISH**

Cast Brass

**LISTED**



**Dimensions:**



- A:** 11.81" (300 mm)
- B:** 6.25" (159 mm)
- C:** 7.63" (194 mm)
- D:** 7.06" (180 mm)



**[ IE28-430T ]**

**4.0" NPT x (2)3.0" NPT - Inline Recessed Brass FDC w. Double Drop Clappers**



**INFORMATION**

Wilson and Cousins' **IE28-430T** is a recessed style inline siamese connection with a 500 GPM inlet capacity, and features a single 4.0" (DN100) NPT outlet and two 3.0" (DN80) NPT inlets. The cast brass body can be used as an auxiliary connection to supplement fire protection water supply systems, and is rated for working pressures up to 250 psi. This connection, with dual independent self-closing clapper valves, can be concealed inside of a building wall during construction. UL/ULC Approved.


**FINISH**

Cast Brass

**LISTED**



**Dimensions:**



<b>A:</b>	11.81"	(300 mm)
<b>B:</b>	7.25"	(184 mm)
<b>C:</b>	7.63"	(194 mm)
<b>D:</b>	5.19"	(131 mm)