




CANADA
ROPE AND TWINE LTD
 Where Tradition and Technology Meet

Kernmantle Static Safety Rope

SPECIFICATION							
DIAMETER		Weight		Minimum Tensile Strength		Recommended Working Load	
Inches	MM	Lb./100ft	Kg./100m	Lbs.	Kg.	Lbs.	Kg.
5/16	8	4.0	5.8	4,800	2,177	960	435
3/8	10	4.6	6.7	5,781	2,622	1,156	524
7/16	11	5.6	8.2	6,676	3,028	1,335	605
1/2	12	6.7	9.8	8,621	3,910	1,724	782



- Balanced-Ply non-rotational inner core and outer sheath (32 Carrier).
- Excellent grip cover.
- Core : 100% Nylon 6.6.(Polyamide)
- Cover : 100% High Tenacity Polyester
- Low Elasticity. (2.0% @ 300 LbF. – 3.9% @ 600 LbF. – 5.8% @ 1000 LbF.)
- Excellent UV and abrasion resistance.
- Specific Gravity : 1.38.(Sinks in water)
- Melting Point 482F – 250C
- Custom lengths available upon request.
- Meets or exceeds NFPA 1983-2017 Technical Use.
- 5:1 recommended working load.
- Good resistance to chemicals.



Canada Rope and Twine Ltd.

155 Bluewater Road, #103,
 Bedford, Nova Scotia, Canada, B4B 1H1.

+1 (902) 835-2253

www.canadarope.com

