



20 LB. ABC MULTIPURPOSE STORED PRESSURE FIRE EXTINGUISHER

DESCRIPTION

Buckeye's 20 LB Monoammonium Phosphate based fire extinguisher is designed for use in combating Class A, B, and C type fires.

Commonly known as an "ABC" fire extinguisher, this multipurpose extinguisher is designed for use in homes, office buildings, warehouses, motor vehicles, farms, and woodworking areas.

(This extinguisher is NOT recommended for use on delicate electronic equipment and computers.)

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards and is DOT compliant. UL and ULC Listed
- US COAST GUARD approved for Type A Size II and Type B:C Size III when used in conjunction with Mounting Bracket Model 811, P/N 700229.
- Polyester epoxy powder coated steel cylinder with anodized all-metal valve assembly.
- ABC dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity: 20 lbs / 9.07 kg

UL/ULC Rating: 10-A:120-B:C

Shipping Weight: 33.5 lbs / 15.2 kg

Height: 21.25 in / 53.8 cm

Width: 8.75 in / 22.2 cm

Cylinder Diameter: 7.5 in / 19.1 cm

Discharge Time: 27 seconds

Discharge Range: 15-21 ft / 4.6-6.4 m

Operating Temperature Range: -65° F to 120° F / -54° C to 49° C

ORDERING INFORMATION

20 LB ABC Dry Chemical Fire Extinguisher with Wall Hook

Aluminum Valve Assembly- P/N 12120 Brass Valve Assembly- P/N 12121

Note: For Coast Guard Approval you must also order the Model 811 Mounting Bracket, P/N 700229

Refer to the Buckeye Spare Parts List for replacement parts