



WILSON & COUSINS
INTERIOR FIRE PROTECTION

4390 PALETTA COURT, UNIT M, BULINGTON, ONTARIO, CANADA L7L 5R2
1 800 270 6792 | FAX: (905) 637 8655 | info@wilsonandcousins.com

[IE33S]

4"x2.5"X2.5" Brass straight body exposed fire department connection



4" (100mm) NPT x 2.5" (65mm) hose thread x 2.5" (65mm) hose thread cast brass straight body exposed fire department connection. The IE33S is a UL / ULC Listed and FM Approved swing clapper body that is used as an auxiliary connection and allows up to 500 GPM to supplement the system water supply for fire protection. The swing clapper provides unobstructed waterway and the exposed design is an economical method of satisfying fire department inlet requirements. Specify regional hose thread for outlet.


FINISH: Cast Brass

OPTIONS: Polish Brass, Cast Chrome or Polish Chrome

HOSE THREADS AVAILABLE: CSA, BCT, WCT, QST, NSST, NPSH, NST, Louisville, Cleveland, Chicago, Pittsburgh, New Cincinnati, New York Corp., New York Fire Department, Richmond and Raleigh



Dimensions:



A= 8.25" (209.55mm)
B= 5.63" (142.95mm)
C= Subject to hose thread
D= Subject to hose thread